

# RAVAS 2100 Exi

Explosion proof pallet truck scale



## BENEFITS

- System certification ATEX II 2 G Ex ib IIB T4 Gb & ATEX II 2 D Ex ib IIIC T135°C Db
- Approval number DEKRA 13ATEX 0044
- Rotating indicator and big push buttons, option
- Exchangeable battery pack
- Stainless steel forks (AISI 304)
- Antistatic steering wheel
- For mixing and batching in zone 1&21 or 2&22!

Top quality

For hazardous areas



# RAVAS


## FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare over the full scale. Pre-set tare maximum first range (200 kg)
- Error messages in display
- Automatic switch-off after 30 minutes of non-use
- Low battery warning in display

## STANDARD SPECIFICATIONS

- Weighing capacity 2,000 kg
- Graduation multirange:  
0 - 200 kg: graduation 0.2 kg  
200 - 500 kg: graduation 0,5 kg  
500 - 2.000 kg: graduation 1 kg
- Max. tolerance 0.1% of the load lifted
- System certification II 2 G Ex ib IIB T4 Gb & II 2 D Ex ib IIIC T135°C Db, approval number DEKRA 13ATEX 0044
- Display LCD, digit height 18 mm
- Keypad foil keypad, 3 function keys, on/off key, resistant to chemicals
- Protection class load cells IP67, indicator IP65
- Fork shoes stainless steel (AISI 304)
- Battery intrinsically safe, approval number DEKRA 13ATEX 0043, 8Vdc/3.5 Ah, rechargeable, exchangeable, maintenance free
- Battery life 100 hours, low battery indication
- Charger 230V/8Vdc - 1 A; for use outside hazardous zone
- Charging time approximately 8 hours
- Steering wheels rubber, antistatic
- Loading wheels polyurethane, tandem
- Colour red (RAL 3000), epoxy painted
- Own weight 145 kg
- Pump quick lift

## DIMENSIONS IN MM



	Standard	Premium*
A Fork length	1150	950 - 2400
B Fork width	170	155
C Minimum fork height	90	86
Space underneath fork	22	
D Maximum fork height	180	176
Lifting height	90	
E Width over forks	555	450 - 900
F Height to top indicator	800	600

\* Selected chassis for non-standard dimensions

For approved versions, class OIML III : European approval no. T2782, switch-of of display when tilting more than 2°. Graduation: multirange 0.5/1 kg, or one of the following fixed graduations:

- 1.000 divisions: 1,0/1.000 kg or 2,0/2.000 kg
- 2.000 divisions: 0,5/1.000 kg or 1,0/2.000 kg

## OPTIONS\*

- Extra exchangeable battery pack
- Data transfer to PDA devices that have Bluetooth® technology
- Legal for trade version, OIML III
- Rotating indicator
- Big push buttons for use with gloves

### RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands

T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

